


Beam-Beam Phenomena in the Tevatron or What We Need to Compensate

Vladimir Shiltsev


Content:

- Original Motivation for the BBC
- Beam-Beam Phenomena:
 - > Beam Loss at 150 and on Ramp
 - > Scallops
 - > Antiproton Lifetime
 - > Proton Lifetime
- Beam-beam compensation
 - > possibilities
 - > requirements

Pbar bunch tunes in collisions - Calc'd




Beam-Beam Compensation Idea



"...to compensate (in average) space charge forces of positively charged protons acting on antiprotons in the Tevatron by interaction with a negative charge of a low energy high-current electron beam "(1997)

Tevatron Electron Lens (TEL-1)



+ HV Modulator, HV+HC PSs, Cryo, QPs, Vacuum, Controls, Diagnostics, Cables

Tevatron Electron Lens at F48




Luminosity and Luminosity Integral

$$L = \frac{3\gamma \ f_0 \ B \ N_{\overline{p}} N_p}{\pi \beta^* (\varepsilon_p + \varepsilon_{\overline{p}})} H(\sigma_l/\beta^*)$$
 see slide

$$I = \int Ldt = N_{stores} \tau_L L_0 \ln(1 + T / \tau_L)$$

- Luminosity Integral: primary factors
 - \triangleright Beta* at IP and bunchlength: $H(x)/beta^*$
 - \succ Emittances $\varepsilon_{p} \, \varepsilon_{pbar}$
 - \triangleright Number of protons: N_p
 - > Number of antiprotons: BN_{pbar}
 - \triangleright Lumi-lifetime: τ_l
 - ➤ Number Stores: N_{store}


Pbar Only Store: <4% loss from Inj to LB




Tevatron Inefficiencies

	10/02	03/03	09/03	02/04	08/04	p/p only
Record Luminosity, e30	36	41	50	63	107	n/a
Protons/bunch	170e9	205e9	245e9	245e9	250e9	same
Pbars/bunch	22e9	23e9	25e9	30e9	39e9	same
P-loss at 150 GeV	14%	10%	8%	5%	4%	5%
Pbar-loss at 150	9%	4%	2%	2%	5%	2%
P-loss on ramp	6%	5%	5%	4%	4%	3% *
Pbar-loss on ramp	8%	11%	8%	6%	8%	2%
Pbar-loss in squeeze	5%	2%	3%	1%	1%	0%
at the beginning of store:						
Pbar lifetime at HEP, hr	~40	~35	~35	~30	~25	~900
Proton lifetime at HEP, hr	~90	~60	~20	~100	~70	~300 *
Eff.emittance lifetime, hr	~14	~26	~31	~16	~16	n/a
Luminosity lifetime, hr	~10	~13	~10	~9	~8	n/a

Total N_aN_p Inefficiency in Tevatron



Luminosity Lifetime in Run II



Lifetime Constituents

$$\tau_L^{-1} = \tau_{\varepsilon}^{-1} + \tau_a^{-1} + \tau_p^{-1} + \tau_H^{-1}$$

$$(15-20) + (20-25) + (35-210) + (70-80) = (7.5-9.0) \text{hrs}$$


- Emittance growth = 90% IBS + 10% Beam-Beam Effects
- Pbar lifetime = (70-80)% burnup + (20-30)% Beam-Beam
- Proton lifetime = 80% Beam-Beam + 20 % burnup
- Hougrlass lifetime = 90% IBS + 10 % Beam-Beam

IBS determines ~50% of the lifetime


Burn-up due to luminosity - another 30-35%

Beam-Beam Interaction reduces lumi-lifetime by 15-20%


Model w/o Beam-Beam and Store 3245




Betatron Tunes (Working Points)




Non-Luminous Antiproton Losses




"Scallops" in Pbar Bunch Emittances




"Scallops": Pbar Emittance




Pbar Bunch Emittance Growth



Measured vs Calc'd Pbar Bunch Tunes




Proton losses induced by Pbars




Bunch #

Pbar bunch intensities and sizes VARY (from AA)



Loss of protons due to pbar non-linearities



Where TEL(s) can be helpful?

Not much at 150 ramp and squeeze:

- > conditions change too fast for present diagnostics and foreseen improvements
- Bunch-by-bunch effects not very prominent (all parasitic IPs are more or less equally important)
- > Too many other important factors to be addressed before BBC (orbits, apertures, vacuum, chromaticities, FWs, helix, etc)


In collisions

- > Some 15-20% of luminosity integral is on stake
- > Scallops
- > Pbar bunch-by-bunch lifetime
- > Proton along-the-train lifetime
- DC beam cleaning at all stages (see below)
 - > 300W CW kicker is nowhere close to TEL efficiency
 - > TEL-2 is needed as an operational spare

So, What about TEL so far?


- Accomplishments to date:
 - > summary below (3 slides only)
 - > XL Zhang, "Experiments with TEL"
- TEL-1 in Operation
 - > XLZhang
- Hardware Issues
 - V.Shiltsev, e-beam hardware
 - > A.Klebaner, cryogenics
 - > M.Olson, BPMs
 - > CYTan, tune measurements
 - > Yu. Tereshkin, HV modulator
- Next Steps, Plans, etc
 - > V.Shiltsev

Tuneshift dQhor=+0.009 by TEL




Three bunches in the Tevatron, the TEL acts on one of them

DC Beam in Abort Gap: TEL On/Off/On



TEL Suppresses Pbar V-Size Growth: ½ hr in store



Prerequisites

Hardware

- > TEL-1 and TEL-2 for full compensation experiments
- Proper e-gun (currently though to be SEFT gun)
- > Powerful enough HV pulser
- > Spares

Diagnostics and Controls

- > BPMs assuring < 0.2 mm e-p or e-a alignment in 4 points
- > A and P bunch-by-bunch tune measurement system with resolution <2e-4 every minute
- ➤ Low-noise A and P bunch-by-bunch monitors intergrated SBDA(P)I(S)S, BOPLOS, DOAHTL, B(D)OILUM, etc
- > ACNET controls, slow feedbacks to track parameters in store

Time

- > To install TEL-2 (>2 wk shutdown)
- > MD studies with TEL-1 and TEL-2